

**LOW COST****HIGH SENSITIVITY****DUAL AIS RECEIVER**

The **RadarPlus® SM161R-2** is a low cost, high sensitivity dual AIS Receiver.

An **Automatic Identification System**, or **AIS**, is an indispensable tool for navigation and safety at sea. Information gathered by the **SM161R-2** is more detailed than radar and enables the everyday boater to see what's coming long before it is in line of sight.

The rugged **SM161R-2** incorporates **increased sensitivity** and **dual stage RF input protection** to provide superior protection against near lightning strikes and high power transmitters.

The **RadarPlus® SM161R-2**:

- Provides high-sensitivity AIS reception
- Receives Class A & B vessel reports
- Interfaces with a PC or chart-plotter
- Consumes less than 1 watt of power

**AIS REPORTS**

- Vessel Name
- Size
- Position
- Course
- Cargo
- And More

**OPTIONAL FEATURES**

- Received Signal Strength Indication
- Ambient Noise Measurement
- Partial Packet Reception
- Packet Time of Arrival
- Slot Numbering
- VDL Loading



**LOW COST****HIGH SENSITIVITY****DUAL AIS RECEIVER****System Specifications**

- **Designation:** Automatic Identification System (AIS) Receiver
- **Serial RS232 interface:** female DB9 connector
- **Power Supply:** 12 to 20 V nominal or 120 – 240 V AC
- **Power Consumption:** Less than 1 watt
- **Temperature Range:** -15 to +55 degrees C.
- **Compass Safe Distance:** 1 meter

**Navigation Specifications**

- **12 channel internal Global Positioning System (GPS) \*OPTIONAL\***
- **GPS antenna interface:** female SMA connector

**Dimensions and Weights**

- **Length:** 6.89 in
- **Width:** 3.15 in.
- **Height:** 2.25 in.
- **Weight:** ≤2 lb.

**Frequencies and Channel Bandwidth**

- **RX AIS1:** 161.975 MHz at 25 kHz
- **RX AIS2:** 162.025 MHz at 25 kHz

**AIS Receivers**

- **AIS Data Rate:** 9,600 bps
- **Sensitivity:** ≤20% PER @ -113 dBm
- **Adjacent Channel Rejection:** 70dB at 25 kHz
- **Blocking:** 80 dB
- **Intermodulation:** 65 dB
- **Large Signal PER:** 1% or less
- **Image Rejection:** ≥ 70 dB for 20% PER
- **Spurious Rejection:** ≥ 70 dB for 20% PER
- **Antenna Interface:** female Type N connector

**Optional: Enhanced Signal Analysis Package**

Enhanced sensitivity with analysis features including:

- Received Signal Strength Indication
- Slot Numbering
- VDL Loading
- Ambient Noise Measurement
- Packet Time of Arrival
- Partial Packet Reception

**Serial Interface Details**

The serial interface of the SM161R-2 conforms to ITU-R M 1371-5 and NMEA 0183 with additional proprietary sentences.

To request full serial interface specifications, please e-mail [info@shinemicro.com](mailto:info@shinemicro.com) or call Shine Micro at (360) 437-2503.

**Software Tested**

The RadarPlus allows AIS enabled software to chart ship positions and descriptions in real-time. The following packages have been tested and are fully operational with the **SM161R-2**:

- Rose Point - **Coastal Explorer**
- ICAN - **Regulus**
- Transas - **NaviSailor**
- Xanatos - **Titan**
- Nobeltec - **Admiral**
- EuroNav – **seaPro**
- Chyna Sea – **MapTech**

**Simple Marine Installation**

1. Mount the SM161R-2 according to the provided mounting diagram.
2. Connect the power cable to a 12 volt power source.
3. Connect a VHF antenna to the Type N connector on the SM161R-2.
4. Connect the serial interface cable to a PC or other AIS display device

**WARRANTY INFORMATION**

Shine Micro warrants its products to be free from defects for one full year from the date of purchase. Shine Micro will, at its sole discretion, repair or replace any components that fail in normal use. Labor and material costs for such repairs or replacement will be free of charge. This warranty does not cover failures due to abuse, misuse, accidents, or unauthorized alterations or repairs.

